

## H07Z1-K

Harmonised single core, 450/750 V  
+70 °C service temperature, low smoke, zero halogen, fire retardant  
EN 50525-3-31 and EN 50575

### Application

Harmonised, zero halogen single core with improved fire characteristics for internal wiring. Zero halogen compound makes this type suitable for installation in environments where smoke and toxic fumes may threaten life or valuable equipment. For fixed and protected installation in devices, control cabinets and in or on lighting equipment.

### Construction



1. Conductor: Copper conductor, bare, flexible (class 5)
2. Insulation: Halogen free thermoplastic compound, different colours

### Technical information

Rated voltage	U <sub>0</sub> /U	450/750 V
Max. permissible temperature at conductor		70°C
Min. operating temperature	fixed installed	-20 °C
Min. temperature during installation		-5 °C
Min. bending radius mm	fixed installed	5 x D outer diameter in mm
<b>Safety parameters</b>		
Reaction to fire		EN 50399 C <sub>ca</sub> - s1, d1, a1
	on request	EN 50399 B2 <sub>ca</sub> - s1a, d1, a1
Flame spread	single cable	IEC 60332-1-2
	bunched cables	IEC 60332-3-24
Halogen free		IEC 60754-1 /-2
Smoke density		IEC 61034-1/ -2

## H07Z1-K

Harmonised single core, 450/750 V  
 +70 °C service temperature, low smoke, zero halogen, fire retardant  
 EN 50525-3-31 and EN 50575

N° of cores and size mm <sup>2</sup>	Insulation thickness approx. mm	Outer-diameter approx. mm	Cable weight approx. kg/km
1 x 1,5	0,7	3,2	22
1 x 2,5	0,8	3,7	33
1 x 4	0,8	3,5	47
1 x 6	0,8	4,7	68
1 x 10	1,0	6,2	114
1 x 16	1,0	7,5	168
1 x 25	1,2	9,5	261
1 x 35	1,2	10,6	350
1 x 50	1,4	12,4	489
1 x 70	1,4	14,7	686
1 x 95	1,6	16,9	951
1 x 120	1,6	18,2	1179
1 x 150	1,8	20,6	1454
1 x 185	2,0	22,7	1828
1 x 240	2,2	25,4	2347

La version française de cette fiche technique est disponible sur demande.  
 De technische gegevens zijn op aanvraag in het Nederlands beschikbaar.