

Traction cable

RADOX TENUIS-TW (EN 50306-4 1P) 600V MM

HUBER+SUHNER

Product description:

RADOX TENUIS-TW (EN 50306-4 1P) 600V MM

Nominal voltage:

Hazard level:

Multicore cables sheathed

600 / 1000 V AC

MM (extra low temperature, extra oil and extra fuel resistant)

General features:

Halogen free electron-beam crosslinked cores with improved behaviour in case of fire, easy to strip and flexible.

Application:

The cables are intended for permanent installation in rail vehicles or for applications in which a limited alternating bending stress occur during service. Guidelines for selection and installation are described in the standards EN 50355 and EN 50343.

General composition of cable:



- | | |
|----------------------|---|
| 1. Filler (optional) | RADOX 125 REC |
| 2. Conductor | Stranded tin plated copper, acc. to EN 50306-2 |
| 3. Insulation | RADOX EI 303, colour: white, unless otherwise specified |
| 4. Wrapping | Tape |
| 5. Sheath | RADOX EM 104, colour: black |

Marking:

[a] **HUBER+SUHNER RADOX TENUIS-TW (EN 50306-4 1P) 600V [b] MM [c]-[d] [e] [f] [g]**

	example:
[a] Meter marking (in m)	= 123456 = m
[b] Cross section (in mm ²)	1X150
[c] Part number	12345678
[d] Batch number	1234567
[e] Production week and year	03-2017
[f] Production place (only if China)	CN
[g] CRCC certification (only if available)	CRCC10218P11529R1M-2

Copyright 2023 HUBER+SUHNER AG. This document may not be amended and its content is confidential. It may not be passed on to third party which are not bound by confidentiality.

The product fulfils the test and specification requirements described in this document for the stated areas of application and operating conditions. HUBER+SUHNER AG does not expressly or implicitly guarantee performance under additional or changed conditions. Deviations are to be agreed upon in writing.

HUBER+SUHNER
Low Frequency Division
CH-8330 Pfäffikon



+41 (0)44 952 22 11
+41 (0)44 952 26 40

www.hubersuhner.com

RADOX TENUIS-TW (EN 50306-4 1P) 600V MM

Technical Data:

Voltage rating cond.-earth	U ₀	600	V AC
Voltage rating cond.-cond.	U	1000	V AC
maximum permissible Voltage rating AC cond.-earth		720	V AC
maximum permissible Voltage rating AC cond.-cond.	U _m	1200	V AC
maximum permissible Voltage rating DC cond.-earth	V ₀	900	V DC
maximum permissible Voltage rating DC cond.-cond.		1500	V DC
Test Voltage		3500	V AC
		8400	V DC
Temperature range		- 50 ... + 125	°C

Min. bending radius

fixed installation	cable diameter ≤ 12 mm	3 x D
	cable diameter > 12 mm	4 x D
sporadic movements	cable diameter ≤ 12 mm	4 x D
	cable diameter > 12 mm	5 x D

NB:

The upper temperature limit is determined by long term ageing according to EN 50305 Par. 7 and extrapolation to 20,000 hours.

The lower temperature limit is determined by bending and elongation tests according to EN 60811-504/505, respectively low temperature behaviour tests for according to GOST 20.57.406-81, method 204-1 and GOST 17491-80.

The specified bending radii require a careful and proper handling using proven fastening technologies.

The cables are in conformity with:

Fire protection on railway vehicles, hazard level . . . HL1 - HL3 EN 45545-2

Vertical flame spread	50 < L ≤ 540 mm	EN 60332-1-2
Vertical flame spread, bunched, D ≤ 6 mm	L ≤ 1.5 m	EN 50305, 9.1.2
Vertical flame spread, bunched, 6 < D < 12 mm	L ≤ 2.5 m	EN 60332-3-25
Vertical flame spread, bunched, D ≥ 12 mm	L ≤ 2.5 m	EN 60332-3-24
Smoke density	T ≥ 70 %	EN 61034-2
Toxicity	ITC ≤ 6	EN 50305, 9.2

Fire protection on railway vehicles Fulfilled NFPA 130

Vertical flame spread, bunched	L ≤ 1.5 m	UL 1685, 12 (FT4 exp.)
Smoke density	TSR ≤ 150 m ² , PSRR ≤ 0.40 m ² /s	UL 1685, 12 (FT4 exp.)

Requirement of hazard level code M (according to EN 50264-1 or EN 50306-1)

Extra low temperature	- 40 °C
Extra oil resistance	IRM 902, 72h, 100 °C
Extra fuel resistance	IRM 903, 168h, 70 °C

Applicable documents:

- 581998 Current rating for multicore cables

RADOX TENUIS-TW (EN 50306-4 1P) 600V MM

Table 1A: Customized Types RADOX TENUIS-TW (EN 50306-4 1P) 600V MM

Cable ¹⁾ Type [n x mm ²]	Conductor ²⁾		Core ²⁾		Cable		Fire Load nom. [kJ/m]	Combustible Material nom. [kg/100m]	Cable Weight nom. [kg/100m]	H+S Part No.
	Ø nom. [mm]	R ₂₀ max. [Ω/km]	Ø nom. [mm]	Colours	Ø [mm]	Colour				
4X0.25	0.60	88.5	1.17	WH	4.5±0.3	BK	322	2.1	3	85064923
4X0.25	0.60	88.5	1.17	WH	4.95±0.15	BK	385	2.7	3.6	85024776 ⁴⁾
3X2X0.25	0.60	88.5	1.17	WH	5.9±0.3	BK	452	3.2	4.5	85204737
2X0.34	0.75	54.7	1.30	WH	3.95±0.3	BK	236	1.7	2.4	85027193
2X0.5	0.84	40.1	1.42	WH	4.4±0.2	BK	290	2.2	3.1	12568036
2V0.5				BN-BU						12584136
3X0.5	0.84	40.1	1.42	WH	4.6±0.2	BK	315	2.2	3.6	12568037
3V0.5				BN-BK-BU						12584137
4X0.5	0.84	40.1	1.42	WH	5.0±0.2	BK	365	2.6	4.4	12568038
4V0.5				BN-BK-BU-WH						12584138
5X0.5	0.84	40.1	1.42	WH	5.5±0.2	BK	473	3.1	5.4	12566304
5V0.5				BN-BK-BU-WH-GY						12585752
6X0.5	0.84	40.1	1.42	WH	6.0±0.2	BK	569	3.7	6.4	12568039
6V0.5				BN-RD-WH-BK-GY-BU						84118473
8X0.5	0.84	40.1	1.42	WH	6.6±0.3	BK	663	4.3	7.7	85100133
9X0.5	0.84	40.1	1.42	WH	7.3±0.3	BK	792	5	9.1	12583000
10X0.5	0.84	40.1	1.42	WH	7.3±0.3	BK	760	5	9.6	85073536
12X0.5	0.84	40.1	1.42	WH	7.6±0.3	BK	862	5.2	10.7	12585961
15X0.5	0.84	40.1	1.42	WH	8.6±0.3	BK	1102	6.6	13.5	12583667
16X0.5	0.84	40.1	1.42	WH	8.6±0.3	BK	1102	6.6	13.9	84096896
25X0.5	0.84	40.1	1.42	WH	10.5±0.4	BK	1623	9.4	20.9	12583001
2X2X0.5	0.84	40.1	1.42	WH	6.8±0.3	BK	630	4.6	6.4	12568040
4X2X0.5	0.84	40.1	1.42	WH	8.5±0.3	BK	966	6.7	10.3	12568041
5X(3X0.5)	0.84	40.1	1.42	WH	14.1±0.4	BK	2880	20.6	31.9	12583566 ⁵⁾
5X(3X0.5)	0.84	40.1	1.42	WH	14.5±0.4	BK	3345	21.5	32.2	85118440 ⁵⁾
6X(3X0.5)	0.84	40.1	1.42	WH	14.6±0.3	BK	3135	21.4	35	12584344 ⁶⁾
2X0.75	1.04	26.7	1.62	WH	4.75±0.3	BK	330	2.4	3.8	12568047
3X0.75	1.04	26.7	1.62	WH	5.15±0.3	BK	380	2.7	4.8	12568048
3G0.75	1.04	26.7	1.62	WH-GNYE	5.15±0.3	BK	380	2.7	4.8	12583990
4X0.75	1.04	26.7	1.62	WH	5.6±0.3	BK	468	3.1	5.9	12568049
4G0.75				WH-GNYE	5.6±0.3	BK				12583992
5G0.75	1.04	26.7	1.62	WH-GNYE	5.75±0.3	BK	495	3.3	6.8	85111986
6X0.75	1.04	26.7	1.62	WH	6.75±0.3	BK	707	4.5	8.7	12568050
6G0.75				WH-GNYE	6.30±0.3	BK	571	3.7	7.6	85143442
8X0.75	1.04	26.7	1.62	WH	7.8±0.3	BK	978	5.9	11.5	12584272
10X0.75	1.04	26.7	1.62	WH	8.1±0.3	BK	935	5.8	12.8	12585274
36X0.75	1.04	26.7	1.62	WH	14.1±0.4	BK	2600	16.1	41.6	85070303
4X2X0.75	1.04	26.7	1.62	WH	9.5±0.3	BK	1200	8.3	13.9	84097783
5X(4X0.75)	1.04	26.7	1.62	WH	18.3±0.5	BK	4700	33.2	53.8	12583090 ⁷⁾
2X1	1.22	20.0	1.77	WH	5.1±0.2	BK	370	2.7	4.5	12568052
2V1				BU-RD						84090409

RADOX TENUIS-TW (EN 50306-4 1P) 600V MM

Cable ¹⁾ Type [n x mm ²]	Conductor ²⁾		Core ²⁾		Cable		Fire	Combustible	Cable	H+S
	Ø nom. [mm]	R ₂₀ max. [Ω/km]	Ø nom. [mm]	Colours	Ø [mm]	Colour	Load nom. [kJ/m]	Material nom. [kg/100m]	Weight nom. [kg/100m]	Part No.
3X1	1.22	20.0	1.77	WH	5.4±0.2	BK	434	2.9	5.6	12568053
3G1				WH-GNYYE						85093498
4X1	1.22	20.0	1.77	WH	5.8±0.2	BK	445	3.1	6.7	12568054
4G1				WH-GNYYE						85106526
5X1	1.22	20.0	1.77	WH	6.65±0.3	BK	580	4.2	8.7	85072779
5G1				WH-GNYYE						85103631
6X1	1.22	20.0	1.77	WH	7.3±0.3	BK	814	5.1	10.5	12568055
7X1	1.22	20.0	1.77	WH	8.0±0.3	BK	994	6.1	12.4	12585459
8X1	1.22	20.0	1.77	WH	8.3±0.3	BK	1093	6.6	13.8	84121018
9G1	1.22	20.0	1.77	WH-GNYYE	8.65±0.3	BK	1101	6.9	15	85110070
10X1	1.22	20.0	1.77	WH	8.7±0.3	BK	1055	6.5	15.5	12581348
12X1	1.22	20.0	1.77	WH	9.1±0.3	BK	1151	6.9	17.7	12584271
16X1	1.22	20.0	1.77	WH	10.4±0.4	BK	1524	9.1	23.5	12584654
19X1	1.22	20.0	1.77	WH	11.6±0.4	BK	1925	11.2	28.4	12585980
25X1	1.22	20.0	1.77	WH	12.8±0.4	BK	2234	13	35.6	12581349
37X1	1.22	20.0	1.77	WH	15.7±0.5	BK	3000	19	52.5	85095097
2X2X1	1.22	20.0	1.77	WH	8.0±0.3	BK	886	6	9.6	12583421
2X1.5	1.45	13.7	2.17	WH	6.0±0.3	BK	520	3.8	6.4	12568098
2V1.5				BU-BN						85170889
3X1.5	1.45	13.7	2.17	WH	6.3±0.3	BK	572	3.9	7.8	12568099
3G1.5				WH-GNYYE						12582026
4X1.5	1.45	13.7	2.17	WH	6.9±0.3	BK	650	4.4	9.6	12568100
4G1.5				WH-GNYYE						12583172
5X1.5	1.45	13.7	2.17	WH	7.8±0.3	BK	884	5.6	12.2	12581350
5G1.5				WH-GNYYE						12582027
6X1.5	1.45	13.7	2.17	WH	8.45±0.3	BK	1058	6.5	14.4	12582028
7X1.5	1.45	13.7	2.17	WH	9.1±0.3	BK	1253	7.6	16.8	12583724
7G1.5				WH-GNYYE						12582029
8X1.5	1.45	13.7	2.17	WH	10.3±0.4	BK	1639	9.9	20.5	12582030
9G1.5	1.45	13.7	2.17	WH-GNYYE	10.6±0.4	BK	1474	9.2	21.1	12584489
10X1.5	1.45	13.7	2.17	WH	10.6±0.4	BK	1443	8.9	22.1	12582031
12X1.5	1.45	13.7	2.17	WH	11.1±0.4	BK	1639	10	25.8	12583725
16X1.5	1.45	13.7	2.17	WH	12.6±0.4	BK	2130	12.7	33.8	12583726
18X1.5	1.45	13.7	2.17	WH	13.4±0.4	BK	2449	14.4	38.2	85063742
20X1.5	1.45	13.7	2.17	WH	14.0±0.4	BK	2599	16.4	41.1	12586297
25X1.5	1.45	13.7	2.17	WH	15.5±0.5	BK	3059	17.9	51	84103977
25G1.5				WH-GNYYE						12582033
30X1.5	1.45	13.7	2.17	WH	16.7±0.5	BK	3606	20.9	60.6	12586298
2X2.5	1.94	8.21	2.75	WH	7.3±0.3	BK	766	5.4	9.8	12568101
2V2.5				BU-BN						85170961
3X2.5	1.94	8.21	2.75	WH	7.8±0.3	BK	854	5.6	12.2	12582034
3G2.5				WH-GNYYE						12582035
4X2.5	1.94	8.21	2.75	WH	8.7±0.3	BK	1049	6.7	15.5	12566306
4G2.5				WH-GNYYE						12583173

RADOX TENUIS-TW (EN 50306-4 1P) 600V MM

Cable ¹⁾ Type [n x mm ²]	Conductor ²⁾		Core ²⁾		Cable		Fire	Combustible	Cable	H+S
	Ø nom. [mm]	R ₂₀ max. [Ω/km]	Ø nom. [mm]	Colours	Ø [mm]	Colour	Load nom. [kJ/m]	Material nom. [kg/100m]	Weight nom. [kg/100m]	Part No.
5X2.5	1.94	8.21	2.75	WH	9.4±0.3	BK	1249	7.7	18.7	12581346
5G2.5				WH-GNYYE						12585007
6X2.5	1.94	8.21	2.75	WH	10.6±0.4	BK	1628	10	23.2	12581347
7G2.5	1.94	8.21	2.75	WH-GNYYE	11.5±0.4	BK	1960	11.9	27.3	12583995
16X2.5	1.94	8.21	2.75	WH	15.8±0.5	BK	3239	19.3	54.6	85002904
20X2.5	1.94	8.21	2.75	WH	17.6±0.5	BK	4126	24	68.1	12585070
30X2.5	1.94	8.21	2.75	WH	20.9±0.5	BK	5418	31.3	97.5	12584363
4X4	2.44	5.09	3.35	WH	10.2±0.4	BK	1442	8.9	22.9	12585458
10X4	2.44	5.09	3.35	WH	16.0±0.5	BK	2108	20.3	55.2	85084353

¹⁾ X: one colour, numbered

G: one green-yellow core, others one colour, numbered

V: various colours

²⁾ Conductor resistance according to EN 50306- 2

³⁾ Construction details of the core is according Technical Datasheet 564264

⁴⁾ increased sheath thickness

⁵⁾ Triples screened, marking 10, 20, 30, 40, 50

⁶⁾ Pairs/Triples screened

⁷⁾ Quad-core no.: 1,4,2,3/ 5,8,6,7/ 9,12,10,11/ 13,16,14,15/ 17,20,18,19